Weave | FANDELIGHT

61010

- Includes One 8" Downrod
- Includes Remote Control
- Color Tunable
- Wifi Enabled







FCT6100WT (Remote Control)



FANDELIGHT™ Magnetically Connect to Wall Plate.


Light Dimming. Battery Operated. *CCT tuning on select SKU's

PRODUCT DESCRIPTION

Bands of metal are woven on a frame and finished in Bronze Gilt on the outside and a contrasting Gold Leaf finish on the inside. An LED light source peers through openings in the weave and directs light outward eliminating any strobing effect that fans may cause. This Fandelight has been updated with a Wi-Fi enabled control that operates color temperature, light intensity and the fan speed. These features can be adjusted by either the remote provided or Smart Home apps.

- Always consult a qualified electrician before installing any lighting product
- Installation Requirements:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding at least 35 lbs



MEASUREMENTS

: 33" D x 18.5" H **DIMENSION**

: 3 x 22" **BLADES** : 18.5" OAH MAX OAH

: 7" W x 2.75" H x 7" L CANOPY

: 28.15 lb HANGING WEIGHT

LAMPING

INPUT VOLTAGE : 120V

: 4,160 Rated (2,700 Del.) **LUMENS**

BULB : 43W LED PCB Intergrated, 43W Total

DIMMABLE : By Control Provided

: 80+ CRI CRI COLOR_TEMP : 3000K

ENERGY INFORMATION AT HIGH SPEED

AIRFLOW : 2600 CFM : 20W **ELECTRICITY USE** AIRFLOW EFFICIENCY : 130 CFM / W

FINISHES OPTION



MATERIAL

Glass+Steel+ABS

RATINGS

CETLUS

Damp Location

INCLUDES

- Wall Mountable Remote Control
- 1 x 8" Downrod

DOWNROD OPTIONS

- 18" (FRD0118SM)
- 24" (FRD0124SM)
- 30" (FRD0130SM) 36" (FRD0136SM)







ADDITIONAL

RATED LIFE: 20,000 Hours OPERATING TEMPERATURE: -20° C (-4°F), 40°C (104°F) LIGHTING DIRECTION: Down



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com