


PRODUCT DESCRIPTION

Step and pathway lighting suitable for interior or exterior application. Designed to install into a single gang box and is line voltage so additional transformers are not needed. Available in Aluminum, White, Black, or Bronze and both horizontal wide beam or vertical narrow beam spread.



MEASUREMENTS

DIMENSION HANGING WEIGHT LAMPING INPUT VOLTAGE LUMENS BULB BULB INCLUDED DIMMABLE CRI COLOR_TEMP : 3.25" W x 3.25" H x 1.5" Ext : 0.44 lb

: 120V : 180 Rated (71 Del.) : 1 x 2W LED PCB Integrated , 2W Total : (Integrated) : Triac CL : 80+ CRI : 3000K

FINISHES OPTION

Bronze (BZ)

Brushed Aluminum (AL)

MATERIAL Die Cast Aluminum

RATINGS Wet Location



ADDITIONAL RATED LIFE 35000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com