

# FLEXIBLE LED FILAMENT I BULBS

**BUL-5W-A50-E26-CL-120V-822 | BUL-5W-BT56-E26-CL-120V-822**

- Available in 2200K color temperature
- Dimmable with Flicker Free
- 110-130 Input Voltage
- Rated life 15,000 lifetime hours
- 5W, 350 Lumens
- ETL/cETL

Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments : \_\_\_\_\_




**A50**



**BT56**

## PRODUCT DESCRIPTION


An innovative acrylic light tower is laser etched to create the effect of a filament bulb. Choose from varying styles that can be installed on any medium base socket. Bulb types range from everyday shapes, such as ST64 or G40, and includes large scale A52 glass types, interesting diamond shapes, and patterned glasses. The glass is hardened making it more durable than average bulbs creating the most robust LED bulbs on the market.



### BULB TYPE: A50

#### MEASUREMENTS

DIMENSIONS : 6.25"D x 11.5"H  
 HANGING WEIGHT : 1.07 Lb



### BULB TYPE: BT56

#### MEASUREMENTS

DIMENSIONS : 7"D x 13.25"H  
 HANGING WEIGHT : 1.38 Lb

#### LAMPING

WATTAGE : 5W  
 INPUT VOLTAGE : 110-130V  
 LUMENS : 350  
 COLOR TEMP. : 2200K  
 BASE TYPE : E26  
 DIMMABLE : Flicker free Dimming

## MATERIAL

Clear Glass

## RATINGS

ETL/cETL



## ADDITIONAL

RATED LIFE: 15,000 Hours  
 OPERATING TEMP: -20° C (-4°), 40°C (104°F)



**WESTERN DISTRIBUTION CENTER (HEADQUARTER)**  
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

**EASTERN DISTRIBUTION CENTER**  
 4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com