WAFER LED 15" I SURFACE MOUNT


57736

- Edge-Lit Technology, evenly distributed light
- Available in 3000K color temperature (See 57737 for 4000K)
- Available in Bronze (BZ), Satin Nickel (SN), and White (WT)
- Dimmable with ELV dimmer at 120V
- 120-277 Input Voltage
- Energy Star listed
- Easy to install: Fits 4" Outlet Box (Pancake NOT recommended)
- Approved for use in closets and storage spaces
- Suitable for Wet location
- ETL/cETL IP65



PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS

DIMENSIONS : 15"L x 15"W x 0.5"H

HANGING WEIGHT : 3.53 Lb MAX OH : 0.5" MIN OH : 0.5" MIN OH : 0.5"

BP Width : 4.1"

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 2500 Rated (2200 Del.)
BULB : (1) 36W PCB LED (Integrated)
DIMMABLE : Dimmable with ELV Dimmer at 120V

CRI : 90+

COLOR TEMPERATURE: 3000K

FINISHES OPTIONS:

White (WT)

Job Name: ___

Quantity : ___

Job Type : _____

Comments:

Bronze (BZ)

Satin Nickel (SN)



MATERIAL:

Aluminum

PMMA Acrylic Diffuser

RATINGS:

ETL/cETL IP65 Wet Location Energy Star








ADDITIONAL:

RATED LIFE: 40,000 Hours OPERATING TEMP: -20° C (-4°), 40°C (104°F)

PHOTOMETRIC: Report Found Online





WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

4200 SHIRLEY DR. I ATLANTA, GA 30336

P. 626.956.4200 | **F**. 626.956.4225 | maximlighting.com