

COVE I Recessed Downlight

57794 / 57796


- LED 3000K, CRI 90+
- 4 inch and 6 inch Recessed Can Substitute
- UL Outlet Box fitted on fixture
- Dimmable with Triac Dimmer
- Good for new construction and remodels
- Indirect lighting into cove for soft-even illumination
- IC-Rated for direct contact with insulation
- Damp Location Rated
- Fire Rated
- ETL/cETL

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



PRODUCT DESCRIPTION


Maxim's Cove recessed downlight series offers a IC Airtight UL rated Outlet Box that is fitted to the fixture for easy installation without the use of a recessed housing. To reduce glare that is associated with other recessed downlights, the Cove uses an innovative concave lens that directs the light upward and is then reflected back down offering even and abundant illumination. Fire Rated and available in standard 120V, Triac dimming, with Color Temperature of 3000K, and CRI of 90+, the Cove is one of the most versatile downlights in the market.



MEASUREMENTS

MODEL	DIMENSION
57794	4.75"D x 3.25"H
57796	6.75"D x 3.75"H

BP HEIGHT	HCO	HANGING WEIGHT
1.85"H	3.30"	0.55 lb
1.85"H	3.80"	0.77 lb



LAMPING

MODEL	BULB TYPE
57794	9W PCB LED (Integrated)
57796	12W PCB LED (Integrated)

CRI	LUMENS	COL TEMP.	DIMMABLE	INPUT
90+	540	3000K	Triac CL	120V
90+	720	3000K	Triac CL	120V

FINISHES OPTIONS:

White (WT)



MATERIAL:

Aluminum

AVAILABLE SIZES:

4" | 6"

RATINGS:

ETL/cETL
 Damp Location
 Energy Star
 IC Airtight
 Fire Rated



ADDITIONAL:

RATED LIFE: 40,000 Hours
 OPERATING TEMP: -20° C (-4°), 40° C (104° F)
 PHOTOMETRIC: Report Found Online
 LIGHTING DIRECTION: Down

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
 4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com