


COUNTERMAX MX-L-120-SL I UNDERCABINET SL

88900 / 88901 / 88902 / 88903 / 88904


- 3000K Color Temperature
- 120-277V input drivers linkable up to 96 watts
- Dimmable at 120V using ELV
- 3/8" tall profile
- CRI 90+
- Suitable for Dry location
- ETL cETL

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



PRODUCT DESCRIPTION

Switch between 3 color temperatures: 4000K, 3000K, and 2700K. All in a 90 CRI for accurate color rendering. The 3K has a patented gimbal designed to allow light to be directed where desired as well as a patented LED strip for even light distribution.



MEASUREMENTS

MODEL	DIMENSION	HANGING WEIGHT	MAX OAH	MIN OAH	BP Width
88900	6"L x 4.5"W x 0.25"H	0.33 LB	0.25"	0.25"	1.90"
88901	12"L x 4.5"W x 0.25"H	1.10 LB	0.25"	0.25"	1.90"
88902	24"L x 4.5"W x 0.25"H	1.87 LB	0.25"	0.25"	1.90"
88903	36"L x 4.5"W x 0.25"H	2.10 LB	0.25"	0.25"	1.90"
88904	48"L x 4.5"W x 0.25"H	2.87 LB	0.25"	0.25"	1.90"

LAMPING

MODEL	BULB TYPE	COLOR TEMP.	LUMENS INIT.	DEL	CRI	INPUT VOLTAGE	DIMMABLE
88900	(1) 3W PCB LED (Integrated)	3000K	210	180	90+	24V	Triac CL
88901	(1) 6W PCB LED (Integrated)	3000K	420	360	90+	24V	Triac CL
88902	(1) 12W PCB LED (Integrated)	3000K	840	720	90+	24V	Triac CL
88903	(1) 18W PCB LED (Integrated)	3000K	1260	1080	90+	24V	Triac CL
88904	(1) 24W PCB LED (Integrated)	3000K	1680	1440	90+	24V	Triac CL

FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)



MATERIAL:

Aluminum

AVAILABLE SIZE:

6" | 12" | 24" | 36" | 48"

RATINGS:

ETL cETL
 Dry Location
 Energy Star



ADDITIONAL:

RATED LIFE: 40,000 Hours
 OPERATING TEMP: -20° C (-4°), 40° C (104° F)
 PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER)

253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com