

COUNTERMAX MX-L-120-3K I UNDERCABINET 3K

89992 / 89993 / 89994 / 89995 / 89996 / 89997

- 3 Color Temperature Options: 4000K, 3000K, and 2700K
- Dimmable using Triac and ELV Dimmers
- Linkable end-to-end or with MX Interlink cord
- Link up to 750 max watts from one supply
- 50,000 hours rated life
- 120° rotation
- CRI 90+
- Suitable for Dry location
- ETL cETL

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____




PRODUCT DESCRIPTION

Switch between 3 color temperatures: 4000K, 3000K, and 2700K. All in a 90 CRI for accurate color rendering. The 3K has a patented gimbal designed to allow light to be directed where desired as well as a patented LED strip for even light distribution.



- Patent gimbals to direct illumination



MEASUREMENTS

MODEL	DIMENSION	HANGING WEIGHT	CRI
89992	6"L x 3.5"W x 1"H	0.36 LB	90+
89993	12"L x 3.5"W x 1"H	1.32 LB	90+
89994	18"L x 3.5"W x 1"H	1.32 LB	90+
89995	24"L x 3.5"W x 1"H	2.26 LB	90+
89996	30"L x 3.5"W x 1"H	2.84 LB	90+
89997	36"L x 3.5"W x 1"H	3.26 LB	90+

LAMPING

MODEL	BULB TYPE	COLOR TEMPERATURE	LUMENS INIT.	DEL	INPUT	DIMMABLE
89992	(1) 3W PCB LED (Integrated)	2700/3000/4000K	200	175	120V	Triac CL
89993	(1) 5W PCB LED (Integrated)	2700/3000/4000K	320	275	120V	Triac CL
89994	(1) 8W PCB LED (Integrated)	2700/3000/4000K	500	450	120V	Triac CL
89995	(1) 12W PCB LED (Integrated)	2700/3000/4000K	750	650	120V	Triac CL
89996	(1) 16W PCB LED (Integrated)	2700/3000/4000K	1000	900	120V	Triac CL
89997	(1) 20W PCB LED (Integrated)	2700/3000/4000K	1250	1100	120V	Triac CL

*Showing lumens based on White (WT) finish


INCLUDES

- 3/8" knockouts on back and bottom
- 9" Connecting cord
- Romex connector
- Mounting screws

Always consult a qualified electrician before installing any lighting product

FINISHES OPTIONS:

- White (WT)
- Bronze (BZ)
- Satin Nickel (SN)



MATERIAL:

Aluminum

AVAILABLE SIZE:

6" | 12" | 18" | 24" | 30" | 36"

RATINGS:

ETL cETL
 Dry Location
 Energy Star
 CA Title 24



ADDITIONAL:

RATED LIFE: 40,000 Hours
 OPERATING TEMP: -20° C (-4°), 40° C (104° F)
 PHOTOMETRIC: Report Found Online

*Photometric data is based on 3000K color temperature on White (WT) finish



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
 4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com

COUNTERMAX MX-L-120-3K I UNDERCABINET 3K ACCESSORIES

Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____



87885 BK, WT
MXInterLink4 Direct Wire Box
2.25"L x 5"W x 1"H



53255
Plastic Wire Clips (Package of 10)
1"L x 0.5"W x 0.25"H



9" **87876 BK, WT**
18" **87877 BK, WT**
24" **87878 BK, WT**
MXInterLink4 Connector Cord



87880 BK, WT
MXInterLink4 Connector Cord 72"
72"L x 1"W x 0.5"H