

WAFER LED 15" I SURFACE MOUNT

57738


- Edge-Lit Technology, evenly distributed light
- Available in 3000K color temperature (See 57739 for 4000K)
- Dimmable with ELV dimmer at 120V
- 120-277 Input Voltage
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Energy Star listed
- Easy to install: Fits 4" Outlet Box
- Not recommended for pancake box
- Suitable for Wet location
- ETL/cETL IP65

Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____



PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.



MEASUREMENTS

DIMENSIONS : 15"L x 15"W x 0.5"H
HANGING WEIGHT : 4.4 lb MAX OH : 0.5"
HCO : 0.5" MIN OH : 0.5"
BP Width : 4.1"

LAMPING

INPUT VOLTAGE : 120-277V
LUMENS : 2500 Rated (2200 Del.)
BULB : 36W PCB LED (Integrated)
DIMMABLE : ELV Dimmer at 120V
CRI : 90+
COLOR TEMPERATURE: 3000K

FINISHES OPTIONS:

White (WT)
Bronze (BZ)
Satin Nickel (SN)



MATERIAL:

Aluminum
PMMA Acrylic Diffuser

RATINGS:

ETL/cETL IP65
Wet Location
Energy Star
Closets Rated: NEC 410.8 & 410.16



ADDITIONAL:

RATED LIFE: 50,000 Hours
OPERATING TEMP: -20° C (-4°), 40°C (104°F)
PHOTOMETRIC: Report Found Online

Always consult a qualified electrician before installing any lighting product



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com