

# COUNTERMAX LITE I UNDERCABINET 5K

UCL-89872 / UCL-89873 / UCL-89874 / UCL-89875 / UCL-89876 / UCL-89877


Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments : \_\_\_\_\_

- 5 Color Temperature Options: 5000K, 4000K, 3500K, 3000K, 2700K
- CRI 90+
- Dimmable using Triac and Electronic Low Voltage Dimmers
- Rated life 35,000 hours
- Linkable end to end or with MX interlink cord
- Link up to 750 max watts from one power supply
- 120° rotation
- Suitable for Closets according to NEC Section 410.8 & 410.16( C ) 5



## PRODUCT DESCRIPTION

Switch between 5 color temperatures: 5000K, 4000K, 3500K, 3000K, and 2700K. All in 90 CRI for accurate color rendering.



## MEASUREMENTS

MODEL	DIMENSION	CRI
89872	8"L x 3" W x 1"H	90+
89873	12"L x 3" W x 1"H	90+
89874	16"L x 3" W x 1"H	90+
89875	24"L x 3" W x 1"H	90+
89876	32"L x 3" W x 1"H	90+
89877	40"L x 3" W x 1"H	90+

## LAMPING

MODEL	BULB TYPE	COLOR TEMPERATURE	LUMENS RATED	DEL	INPUT	DIMMABLE
89872	3W LED (Integrated)	27-30-35-40-50 K	300	190	120V	Triac or ELV
89873	6W LED (Integrated)	27-30-35-40-50 K	500	350	120V	Triac or ELV
89874	8W LED (Integrated)	27-30-35-40-50 K	700	500	120V	Triac or ELV
89875	12W LED (Integrated)	27-30-35-40-50 K	1000	750	120V	Triac or ELV
89876	16W LED (Integrated)	27-30-35-40-50 K	1300	1100	120V	Triac or ELV
89877	20W LED (Integrated)	27-30-35-40-50 K	1600	1300	120V	Triac or ELV

## INCLUDES

- 3/8" knockouts on back and bottom
- Romex connector
- Mounting screws

Always consult a qualified electrician before installing any lighting product

## OPTIONAL



**MXInterLink4 Connector Cord**  
 9" 87876 BK, WT  
 12" 87875 BK, WT  
 18" 87877 BK, WT  
 24" 87878 BK, WT



**Plastic Wire Clip**  
 53255  
 1"L x .5"W x .25"H  
 • Package of 10



**MXInterLink4 Power Cord**  
 87880 BK, WT  
 72"L



**MXInterLink4 Direct Wire Box**  
 87885 BK, WT  
 6.5"L x 2.75"W x 1"H

## FINISHES OPTION



## MATERIAL

Aluminum + PC

## AVAILABLE SIZE:

8" | 12" | 16" | 24" | 32" | 40"

## RATINGS

cETLus  
 Dry Location  
 CA Title 24



## ADDITIONAL

INSTALL UP/DOWN: Down  
 RATED LIFE 35000 Hours  
 OPERATING TEMPERATURE:  
 -20°C (-4°F), 40°C (104°F)



WESTERN DISTRIBUTION CENTER (HEADQUARTER)  
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER  
 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com