Quantity:



PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Either sharply angled or smoothly sloping, this discreet architectural light source is also available with various photocell and motion sensor options. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor rated powder coat finishes.

MEASUREMENTS

DIMENSION BACK PLATE HANGING WEIGHT : 5.5" W x 7" H x 4" Ext : 4.25" HCO : 2.31 lb

LAMPING

INPUT VOLTAGE : 120-277V LUMENS : 1,050 Rated (750 Del.) BULB : 1 x 15W LED DC Integrated , 15W Total BULB INCLUDED : (Integrated) DIMMABLE : Triac or ELV at 120V CRI : 90 CRI COLOR_TEMP : 3000K LIGHTING_DIRECTION : Down

FINISHES OPTION



MATERIAL Aluminum

RATINGS

cETLus Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Down RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com