Quantity:



PRODUCT DESCRIPTION

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Either sharply angled or smoothly sloping, this discreet architectural light source is also available with various photocell and motion sensor options. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor rated powder coat finishes.

MEASUREMENTS

DIMENSION BACK PLATE HANGING WEIGHT : 7" W x 4.5" H x 3.5" Ext : 2.25" HCO : 1.51 lb

LAMPING

INPUT VOLTAGE: 120-277VLUMENS: 880 Rated (820 Del.)BULB: 1 x 15W LED PCB IntegBULB INCLUDED: (Integrated)DIMMABLE: Only at 120V with ELVCRI: 80 CRICOLOR_TEMP: 3000KLIGHTING_DIRECTION : Down

: 1.51 lb : 120-277V : 880 Rated (820 Del.) : 1 x 15W LED PCB Integrated , 15W Total : (Integrated)

) PCB Integrated , 15W Toto) V with ELV

FINISHES OPTION



MATERIAL Aluminum +Acrylic

RATINGS

cETLus Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Down PHOTOCELL RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com