Quantity:



## **PRODUCT DESCRIPTION**

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Either sharply angled or smoothly sloping, this discreet architectural light source is also available with various photocell and motion sensor options. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor rated powder coat finishes.

# MEASUREMENTS

DIMENSION BACK PLATE HANGING WEIGHT : 7" W x 4.5" H x 3.5" Ext : 2.25" HCO : 1.51 lb

### LAMPING

INPUT VOLTAGE: 120-277VLUMENS: 880 Rated (820 Del.)BULB: 1 x 15W LED PCB Integrated , 15W TotalBULB INCLUDED: (Integrated)DIMMABLE: Only at 120V with ELVCRI: 80 CRICOLOR\_TEMP: 3000KLIGHTING\_DIRECTION : Down





MATERIAL Aluminum +Acrylic

# RATINGS

cETLus Wet Location ADA



#### ADDITIONAL

INSTALL UP/DOWN: Down PHOTOCELL RATED LIFE 50000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com