Job Type:_



PRODUCT DESCRIPTION

8"

With solid Die-Cast Aluminum construction and powered by a range voltage input driver, Pathfinder is a high performance down light for commercial and residential installations. Either sharply angled or smoothly sloping, this discreet architectural light source is also available with various photocell and motion sensor options. Choose from Black, Architectural Bronze, or Metallic Sliver outdoor rated powder coat finishes.

MEASUREMENTS

4" "HCO	

	4" *HCO
9"	<u> </u>

*height from center of outlet to the top of the fixture

DIMENSION

: 9" W x 8" H x 4" Ext BACK PLATE : 4" HCO HANGING WEIGHT : 3.08 lb

LAMPING

CRI

INPUT VOLTAGE :120-277V LUMENS : 2,000 Rated (1,500 Del.) BULB : 1 x 20W LED DC Integrated , 20W Total BULB INCLUDED : (Integrated) DIMMABLE : Triac or ELV at 120V : 90 CRI : 3000K COLOR_TEMP LIGHTING_DIRECTION : Down

FINISHES OPTION



MATERIAL

Aluminum

RATINGS

cETLus Wet Location ADA



ADDITIONAL

INSTALL UP/DOWN: Down RATED LIFE 25000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com