

COUNTERMAX MX-LD-D I UNDERCABINET LED DISC

53860


- Surfaced or Recessed installation with 30° swivel
- Available in 3000K Color Temperature, CRI 80+
- Dimmable using standard dimmer
- 35000 rated life hours
- Two 12" wire leads (Black for Anodized Bronze (BRZ) and Brushed Aluminium (AL) finishes, White for White (WT) finish)
- Twist lock connectors
- 24V low voltage lighting system
- Frosted light guard diffuser
- Up to 9 MX-LD-D LED Discs on a single 30W driver (53879BK) and up to 6 MX-LD-D LED Discs on single 20W driver (53878BK)

Job Name : _____
 Job Type : _____
 Quantity : _____
 Comments : _____



PRODUCT DESCRIPTION

The versatile CounterMax® MX-L-D LED disc features two piece aluminum construction that allows for both surface mounting or recessed installation and are designed for daisy chain installation of up to nine discs on one driver with direct-wire installation. MX-L-D LED discs operate at a fraction of the heat of a halogen or xenon discs and consume less than three watts of electricity. When used in conjunction with the available dimmable driver, MX-L-D LED discs are dimmable using a standard dimmer. This combination of versatility, safety, energy efficiency and dimmability make the MX-L-D LED discs the smart choice for disc lighting.



MEASUREMENTS

DIMENSIONS : 2.75"D x 0.5"H
 HANGING WEIGHT : 0.19 lb


LAMPING

INPUT VOLTAGE : 24V
 LUMENS : 220 Rated
 BULB : (1) 2.3W PCB LED (Integrated)
 DIMMABLE : Triac CL
 CRI : 80+

Always consult a qualified electrician before installing any lighting product

INCLUDES:

- Two clear mount clips with 3M Tape
- Two mounting screws



Two piece Aluminum Construction for both Surface and Recessed Installation

OPTIONAL



Extension Cords
 12" **53868 BK, WT**
 24" **53869 BK, WT**



53874
 24V 24W Plug-In Driver



Cls II Dim Direct Wire Driver
 20W **53878, BK**
 30W **53879, BK**



Extension Cords
 12" **53887 BK, WT**
 24" **53869 BK, WT**

FINISHES OPTIONS:

- White (WT)
- Anodized Bronze (BRZ)
- Brushed Aluminium (AL)



MATERIAL:

Aluminum
 Frosted Acrylic Lens

RATINGS:

ETL/cETL
 DRY Location



ADDITIONAL:

ROTATION : 30° SWIVEL
 RATED LIFE : 35,000 Hours
 OPERATING TEMP : -20° C (-4°), 40° C (104° F)
 PHOTOMETRIC : Report Found Online



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
 4200 SHIRLEY DR. | ATLANTA, GA 30336

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com