

# CHIP | RD FLUSH MOUNT

57590 | 57591 | 57592 | 57593 | 57594 | 57596 | 57597


- Size options: 5.5", 6", 7", 9", and 11"
- Available in 3000K (Made-to-order Color Temperatures available)
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in Black (BK), Satin Nickel (SN) and White (WT)
- Dimmable with Triac and ELV Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box (**Pancake and mud ring acceptable**)
- Edge-Lit LED Technology
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- IP54 Rating

Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments : \_\_\_\_\_



## PRODUCT DESCRIPTION

This low profile flush mount is our entry level Wafer. Manufactured of a plastic shell with aluminum backing, the Chip brings all the look of the Wafer at economical pricing for residential applications. The bright and even lighting effect is delivered by edge-lit technology offering an upscale surface mount solution to substitute recessed can lighting. Use the optional pendant adapter to convert any size to a hanging fixture.



## MEASUREMENTS

MODEL	DIMENSION
57590	5.5"W x 1.25"H x 5.5"L
57591	5.75"W x 0.75"H x 5.75"L
57592	7"L x 7"W x 1.25"H
57593	7"W x 0.75" H x 7"L
57594	9"W x 1.25" H x 9"L
57596	11.25"W x 0.75" H x 11.25"L
57597	11.25"W x 0.75" H x 11.25"L

## LAMPING

BULB TYPE	CRI	COL TEMP.	LUMENS DEL	DIMMABLE	INPUT
11W PCB Integrated LED	90+	3000K	700	Triac CL/ELV	120V
12W PCB Integrated LED	90+	27-30-35-40-50K	700	Triac CL/ELV	120V
15W PCB Integrated LED	90+	3000K	1050	Triac CL/ELV	120V
16W PCB Integrated LED	90+	27-30-35-40-50K	950	Triac CL/ELV	120V
18W PCB Integrated LED	90+	3000K	1200	Triac CL/ELV	120V
26W PCB Integrated LED	90+	3000K	1500	Triac CL/ELV	120V
26W PCB Integrated LED	90+	27-30-35-40-50K	1500	Triac CL/ELV	120V

## FINISHES OPTIONS:



## MATERIAL:

Polycarbonate + Steel

## GLASS:

White

## AVAILABLE SIZE:

5.5" | 6" | 7" | 9" | 11"

## RATINGS:

cETLus  
 Wet Location  
 Title 24 JA8 Compliant  
 Energy Star  
 ADA



## ADDITIONAL:

INSTALL UP/DOWN: UP  
 RATED LIFE: 50,000 hours  
 OPERATING TEMPERATURE:  
 -20°C (-4°F), 40°C (104°F)  
 WIRE LENGTH 8"L

Always consult a qualified electrician before installing any lighting product



### WESTERN DISTRIBUTION CENTER (HEADQUARTER)

253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

### EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com