# TRIM I FLUSH MOUNT

## 57660 | 57662 | 57663 | 57664

- Die Cast Aluminum Construction
- Size options between 5", 7", 9", and 11"
- Ultra-thin 1" height with less than 1/4" trim
- Available in 3000k (Made-to-order Color Temperatures available)
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Forward Phase Dimming
- Easy to install: fits in 3-0 and 4-0 Outlet Box (pancake and mud ring acceptable)
- Suitable for Wet Location, for use on ceilings outdoor and above showers
- ETL/cETL IP65












MSC8766 Mud-in Ring

## **PRODUCT DESCRIPTION**

Thin discs of evenly illuminated LED create the impression of recessed lighting. The die-cast aluminum housings are available in White, Black, Satin Nickel, and Polished Chrome all with a thoughtfully recessed White polycarbonate diffuser. High efficiency and good color rendering make this a perfect choice for your next project.





#### **MEASUREMENTS**

MODEL	DIMENSION	DRIVER	CANOPY	WIRE LENGHT
57660	5"W x 0.75"H x 5"L	0.75"H	5"W x 0.75"H x 5"L	8"L
57662	7"W x 0.75"H x 7"L		7"W x 0.75"H x 7"L	8"L
57663	9"W x 0.75"H x 9"L		9"W x 0.75"H x 9"L	8"L
57664	11"W x 0.75"H x 11"L		11"W x 0.75"H x 11"L	8"L
MSC8766	4.25"W x 0.5"H			

## **LAMPING**

			COL	LUME	ENS		
MODEL	BULB TYPE	CRI	TEMP.	<b>RATED</b>	DEL	DIMMABLE	INPUT
57660	12.5W AC Integrated LED	90+	3000K	920	875	Triac CL	120V
57662	15W AC Integrated LED	90+	3000K	1100	1050	Triac CL	120V
57663	18W AC Integrated LED	90+	3000K	1500	1450	Triac CL	120V
57664	20W AC Integrated LED	90+	3000K	1600	1500	Triac CL	120V

Always consult a qualified electrician before installing any lighting product

### **FINISH OPTIONS:**

Polished Chrome(PC) Satin Nickel (SN)

White (WT)

Black (BK)



PC + Aluminum

#### GLASS:

White Acrylic (WT)

### **AVAILABLE SIZES:**

5" | 7" | 9" | 11"

#### **RATINGS:**

**CETLUS** Wet Location Dimmable Title 24 JA8 Compliant **Energy Star** ADA











### **ADDITIONAL:**

RATED LIFE: 35,000 hours WARRANTY: 5 Years

