WAFER LED I FLUSH/WALL MOUNT

58720 / 58722 / 58724 / 58738 / 58739

- Patent Pending Construction
- 120 - 277 input
- Die Cast Aluminum
- Size options: 5", 7", 9", and 15"
- Ultra thin 0.5" H
- Approved for use in closets and storage spaces
- Suitable for Closets according to NEC Section 410.8 & 410.16
- Available in White (WT), Bronze (BZ), and Satin Nickel (SN)
- Triac Dimmable with Electronic Low Voltage Dimmers
- Easy to install: fits in 3-0 and 4-0 Outlet Box
- Edge-Lit LED Technology
- Suitable for Wet Location
- ETL/cETL IP65

Job Name : _____
Job Type : _____
Quantity : _____
Comments : _____

PRODUCT DESCRIPTION

Wafer was designed for the discriminate consumer who wants the low profile look of recessed without the high cost. Manufactured of die cast aluminum, Wafer brings ultimate heat dissipation to its edge lit technology. Edge lighting gives very even light distribution while dispersing heat over a larger area. The result of this is longer LED life and better light diffusion.

FINISHES OPTIONS:

White (WT)
Bronze (BZ)
Satin Nickel (SN)
Black (BK)

MATERIAL:
Die Cast Aluminum
PMMA Acrylic Diffuser

AVAILABLE SIZES:
5" | 7" | 9"| 15"

RATINGS:
ETL/cETL IP65
Wet Location
Energy Star
Title 24 JA8 compliant
ADA
Closets Rated: NEC 410.8 & 410.16

ADDITIONAL:
RATED LIFE: 50,000 Hours
OPERATING TEMP: -20° C (-4°), 40°C (104°F)
PHOTOMETRIC: Report Found Online

MEASUREMENTS

LAMPING

MODEL	DIMENSION	WIRE LENGHT	MODEL	BULB TYPE	CRI	LUMENS RATED	DEL	COL TEMP.	DIMMABLE	INPUT
58720	5"L x 5"W x 0.5"H	6"L	58720	10W PCB LED (Integrated)	90+	800	650	3000K	ELV	120V -277
58722	7"L x 7"W x 0.5"H	6"L	58722	15W PCB LED (Integrated)	90+	1250	1000	3000K	ELV	120V -277
58724	9"L x 9"W x 0.5"H	6"L	58724	20W PCB LED (Integrated)	90+	2250	1800	3000K	ELV	120V -277
58738	15"L x 15"W x 0.5"H	6"L	58738	30W PCB LED (Integrated)	90+	3000	2400	3000K	ELV	120V -277
58739	15"L x 15"W x 0.5"H	6"L	58739	30W PCB LED (Integrated)	90+	3000	2400	4000K	ELV	120V -277

Always consult a qualified electrician before installing any lighting product