




PRODUCT DESCRIPTION

Linear EE collection's commercial grade energy efficient lighting features linear frames of metal finished in Satin Nickel and White acrylic diffusers. High Power Factor ballasts allow for commercial applications and the fluorescent light source ensure low maintenance and energy cost savings. Specific styles of Linear EE are also available with a LED light source in the Linear LED collection.



MEASUREMENTS

DIMENSION : 36" W x 6" H x 4" Ext
 BACK PLATE : 2.74" W x 35.17" H x 2.25" HCO
 HANGING WEIGHT : 6.02 lb

LAMPING

INPUT VOLTAGE : 120V
 LUMENS : 4,300 Rated
 BULB : 2 x 25W Fluorescent Med Bi Pin T8 , 50W Total
 BULB INCLUDED : (Not Included)
 DIMMABLE : No

FINISHES OPTION

 Satin Nickel (SN)

GLASS

White WT

MATERIAL

Metal

RATINGS

cETLus
 Damp Location
 CA Title 24
 ADA



ADDITIONAL

INSTALL UP/DOWN: All
 INCANDESCENT WATTS: 436
 RATED LIFE 10000 Hours
 OPERATING TEMPERATURE:
 -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER
 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com