Job Type:



PRODUCT DESCRIPTION

This classic cylinder design has been made ultra-thin intending its use in applications requiring ADA compliance. The sconce casts generous lighting both upwards and downwards using dedicated, high-powered LED. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications. Available in Matte Black, Architectural Bronze and White outdoor powder coat finishes. For Dark Sky applications, make use of the optional Dark Sky Cap available.

MEASUREMENTS

LUMENS

BULB

CRI

15"	17″
5″	

DIMENSION : 2.5" L x 2.5" W x 15" H : 136.5" OAH MAX OAH CANOPY : 5" W x 0.25" H x 5" L HANGING WEIGHT : 2.42 lb LAMPING INPUT VOLTAGE : 120-277V : 700 Rated (640 Del.) : 1 x 7W LED DC Integrated , 7W Total BULB INCLUDED : (Integrated) DIMMABLE : Triac or ELV at 120V : 90 CRI COLOR_TEMP : 3000K

FINISHES OPTION



MATERIAL

Aluminum, Glass

RATINGS

CETLUS Damp Location CA Title 24



ADDITIONAL

RATED LIFE 25000 Hours OPERATING TEMPERATURE: -20°C (-4°F), 40°C (104°F)

PHOTOMETIC: Report Found Online

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com