

# COUNTERMAX 5K I UNDERCABINET 5K

**89862/ 89863/ 89864/ 89865/ 89866/ 89867**

- 5 Color Temperature Options: 5000K, 4000K, 3500K, 3000K, 2700K
- CRI 90+
- Dimmable using Triac and Electronic Low Voltage Dimmers
- Rated life 40,000 hours
- Linkable end to end or with MX interlink cord
- Link up to 750 max watts from one power supply
- 120° rotation
- Suitable for Closets according to NEC Section 410.8 & 410.16 ( C ) 5

Job Name : \_\_\_\_\_  
 Job Type : \_\_\_\_\_  
 Quantity : \_\_\_\_\_  
 Comments : \_\_\_\_\_




## PRODUCT DESCRIPTION

Switch between 5 color temperatures: 5000K, 4000K, 3500K, 3000K, and 2700K. All in 90 CRI for accurate color rendering. The 5K has a patented gimbal designed to allow light to be directed where desired.



- Patent gimbals to direct illumination



## MEASUREMENTS

MODEL	DIMENSION	CRI	HCO
89862	6"L x 3.5" W x 1"H	90+	0.75
89863	12"L x 3.5" W x 1"H	90+	0.75
89864	18"L x 3.5" W x 1"H	90+	0.75
89865	24"L x 3.5" W x 1"H	90+	0.75
89866	30"L x 3.5" W x 1"H	90+	0.75
89867	36"L x 3.5" W x 1"H	90+	0.75

## LAMPING

MODEL	BULB TYPE	COLOR TEMPERATURE	LUMENS RATED	DEL	INPUT	DIMMABLE
89862	3W LED (Integrated)	5000K	360	198	120V	Triac CL
89863	6W LED (Integrated)	5000K	720	460	120V	Triac CL
89864	10W LED (Integrated)	5000K	1200	930	120V	Triac CL
89865	13W LED (Integrated)	5000K	1560	1150	120V	Triac CL
89866	15W LED (Integrated)	5000K	1800	1420	120V	Triac CL
89867	19W LED (Integrated)	5000K	2220	1730	120V	Triac CL

## INCLUDES

- 3/8" knockouts on back and bottom
- Romex connector
- Mounting screws

*Always consult a qualified electrician before installing any lighting product*

## OPTIONAL



**MXInterLink4 Connector Cord**  
 9" 87876 BK, WT  
 12" 87875 BK, WT  
 18" 87877 BK, WT  
 24" 87878 BK, WT



**Plastic Wire Clip**  
 53255  
 1"L x .5"W x .25"H  
 • Package of 10



**MXInterLink4 Power Cord**  
 87880 BK, WT  
 72"L



**MXInterLink4 Direct Wire Box**  
 87885 BK, WT  
 6.5"L x 2.75"W x 1"H

## FINISHES OPTION

- Bronze
- Satin Nickel
- White

## MATERIAL

Aluminum + LED + PC

## AVAILABLE SIZE:

6" | 12" | 18" | 24" | 30" | 36"

## RATINGS

- cETLus
- Dry Location Energy Star
- JA8 Listed



## ADDITIONAL

RATED LIFE 40000 Hours  
 OPERATING TEMPERATURE:  
 -20°C (-4°F), 40°C (104°F)



WESTERN DISTRIBUTION CENTER (HEADQUARTER)  
 253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER  
 101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com